TINMAR INVER

info@tinmarinver.com
www.tinmarinver.com
C/ De la Farigola, 12
08755 Castellbisbal
(Barcelona) SPAIN



CPR: Cca -s1a, d1, a1

Reference Numbers:

002-1051501	2x1.0	mm^2
002-1051601	2x1.5	mm^2
002-1051701	2x2.5	mm^2

Standards and Compliance:

UNE EN 50575/A1:2016
UNE EN 60332-1-2
IEC EN 60754-2
IEC 61034-2
IEC 60228
RoHS Compliant

DETECFIRE COM YY DATASHEET Z1Z1-K (AS)

Description:
For indoor installations where protecting human health and facilitating evacuation in the event of a fire is either recommended or mandatory. The LSZH (Low Smoke Zero Halogen) thermoplastic polyolefin insulation ensures excellent fire performance, significantly reducing fire spread.

PHYSICAL CHARACTERISTICS:

Conductor: Class 5 Flexible Copper (IEC 60228)
- **Cross Section:** 1/1.5/2.5 mm^2

Insulation: LSZH EVA Polyolefin
- **Color:** Red, Black
- **Core Diameter:** 2.8 mm

Twist Rate: Twisted Pair ≥ 25 twists/m

Jacket: LSZH EVA Polyolefin
- **Color:** Red

Overall Diameter: 7.8/8.8 mm

ELECTRICAL CHARACTERISTICS:

Capacitance: 86 pF/m
Characteristic Impedance: 120 Ω ±10%
Operating Voltage: 300V/500V
Operating Temperature: -20ºC/+70ºC
Test Voltage: 2000V DC > 1 Min

This document Is informative, and has no contractual obligation and can be modified without any notification.